



コネクター取付け穴
 $\phi 27.5$ n個

断面A-A

1

2

3

50 50 50 50

10- $\phi 5$

4- $\phi 10.5$

補強リブ

250

50 50 50 50 50 50

150

50

25

A

15

15

(75)

1.6

The drawing shows a rectangular plate with a grid of holes. The overall dimensions are 250 (width) by 150 (height). There are 10 holes of diameter 5 (10-φ5) arranged in a 2x5 grid. There are 4 holes of diameter 10.5 (4-φ10.5) arranged in a 2x2 grid. The plate has a thickness of 1.6. A cross-section A-A is indicated at the bottom. The cross-section shows a U-shaped profile with a width of 75 and a height of 150. The plate is labeled with 'コネクター取付け穴 φ27.5 n個' (Connector mounting hole φ27.5 n pieces) and '断面A-A' (Section A-A). The drawing includes various dimension lines and labels for holes and sections.

3	十字穴付なべ小ねじ	SUS304	4	M5×6
2	ブACKET S-S	SPHC	2	黒色防錆塗装
1	パネル	SPHC	1	黒色防錆塗装
部番	部 品 名 称	材 質	数量	備 考
承認	検図	照合	形式	ヘッダパネル シングル
			図面名称	
単位 mm Free	製図	写図	コード	
第三角法	横溝	田崎 横溝	図表中に記載	
	'00.10.17	'04.9.27		
前澤給装工業株式会社			図番	3-CP0025